SAFETY DATA SHEET Temporary Line Marker (GB)

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Temporary Line Marker (GB)

Product number Code-Nr. BA-SP02

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Technical Aerosol.

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Blue Diamond S.T.L.

Sandall Stones Road, Kirk Sandall Industrial Estate,

Doncaster, DN3 1QR United Kingdom

Tel: +44(0) 1302 310113 Email: sales@bdstl.com

1.4. Emergency telephone number

Emergency telephone +44(0) 1302 310113

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated

Precautionary statements P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use. P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

Temporary Line Marker (GB)

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Dimethyl ether 25 - <50%

CAS number: 115-10-6 EC number: 204-065-8

Classification

Flam. Gas 1 - H220

Press. Gas, Liquefied - H280

Calcium carbonate 10 - <25%

CAS number: 471-34-1 EC number: 207-439-9

Substance with National workplace exposure limits.

Classification

Not Classified

Ethanol 10 - <25%

CAS number: 64-17-5 EC number: 200-578-6

Classification

Flam. Liq. 2 - H225 Eye Irrit. 2 - H319

Titanium dioxide 10 - <25%

Substance with National workplace exposure limits.

Classification

Not Classified

Dimethoxymethane 5 - <10%

CAS number: 109-87-5 EC number: 203-714-2

Classification

Flam. Liq. 2 - H225

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information If in doubt, get medical attention promptly.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if any

discomfort continues.

Temporary Line Marker (GB)

Ingestion Rinse mouth thoroughly with water. Do not induce vomiting unless under the direction of

medical personnel. Get medical attention if any discomfort continues.

Skin contact Remove contaminated clothing and rinse skin thoroughly with water. Get medical attention if

any discomfort continues.

Eye contact Remove any contact lenses and open eyelids wide apart. Wash with plenty of water. Continue

to rinse for at least 10 minutes. Get medical attention if any discomfort continues.

Protection of first aidersFirst aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Vapours/aerosol spray may irritate the respiratory system. Vapours may cause headache,

fatigue, dizziness and nausea.

Ingestion May cause discomfort if swallowed.

Skin contact Prolonged skin contact may cause redness and irritation.

Eye contact Vapour or spray in the eyes may cause irritation and smarting.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide or dry

powder. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

products

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Extremely flammable aerosol. Containers can burst violently or explode when heated, due to

excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. In use may form flammable/explosive vapour-air mixture.

Hazardous combustion

Thermal decomposition or combustion products may include the following substances:

Harmful gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting

Evacuate area. Fight fire from safe distance or protected location. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control runoff water by containing and keeping it out of sewers and watercourses. Avoid breathing fire gases or vapours.

Special protective equipment for firefighters

Use protective equipment appropriate for surrounding materials. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Temporary Line Marker (GB)

Personal precautions

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Evacuate area.

No smoking, sparks, flames or other sources of ignition near spillage. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant.

Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. If ventilation is inadequate, suitable respiratory protection must be worn.

Do not touch or walk into spilled material. Wash thoroughly after dealing with a spillage.

6.2. Environmental precautions

Environmental precautions

Do not discharge into drains or watercourses or onto the ground. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

No smoking, sparks, flames or other sources of ignition near spillage. Eliminate all ignition sources if safe to do so. Provide adequate ventilation. Wash thoroughly after dealing with a spillage.

Approach the spillage from upwind. Absorb spillage with non-combustible, absorbent material. The contaminated absorbent may pose the same hazard as the spilled material. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Dispose of contents/container in accordance with national regulations.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from food, drink and animal feeding stuffs. Do not pierce or burn, even after use. In use may form flammable/explosive vapour-air mixture.

Provide adequate ventilation. Avoid inhalation of vapours/spray and contact with skin and eyes. Vapours may accumulate on the floor and in low-lying areas.

Use only non-sparking tools. Take precautionary measures against static discharges. Use explosion-proof electrical, ventilating and lighting equipment.

Advice on general occupational hygiene

Good personal hygiene procedures should be implemented.

Do not eat, drink or smoke when using this product. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Take off contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Keep only in the original container in a cool, well-ventilated place. Store at temperatures not exceeding 50°C/122°F. Avoid exposure to high temperatures or direct sunlight. Keep away from heat, sparks and open flame. Keep out of the reach of children.

Temporary Line Marker (GB)

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Dimethyl ether

Long-term exposure limit (8-hour TWA): WEL 400 ppm 766 mg/m³ Short-term exposure limit (15-minute): WEL 500 ppm 958 mg/m³

Calcium carbonate

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

Ethanol

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m³

Titanium dioxide

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Dimethoxymethane

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 3160 mg/m³ Short-term exposure limit (15-minute): WEL 1250 ppm 3950 mg/m³ WEL = Workplace Exposure Limit

8.2. Exposure controls

Appropriate engineering

controls

Observe any occupational exposure limits for the product or ingredients.

Provide adequate general and local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid inhalation of vapours and spray/mists.

Use explosion-proof ventilating equipment.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Tight-fitting safety glasses. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. For exposure up to 8 hours, wear gloves made of the following material: Butyl rubber. Thickness: 0.7 mm

Frequent changes are recommended.

Other skin and body protection

should be worn if a risk assessment indicates skin contamination is possible.

Hygiene measures

 $\label{eq:conditional} \textbf{Good personal hygiene procedures should be implemented.} \ \textbf{Do not eat, drink or smoke when}$

Appropriate footwear and additional protective clothing complying with an approved standard

using this product.

Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Take off contaminated clothing and wash it before reuse.

Temporary Line Marker (GB)

Respiratory protectionUse only outdoors or in a well-ventilated area. Respiratory protection complying with an

approved standard should be worn if a risk assessment indicates inhalation of contaminants is

possible.

If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator

fitted with the following cartridge: Gas filter, type AX.

Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked.

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Residues and empty containers should be taken care of as hazardous waste according to local and national

provisions.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Colour Various colours.

Odour Solvent.

pH Not determined.

Melting point Not determined.

Initial boiling point and range Not determined.

Flash point Not determined.

Evaporation rate Not determined.

Flammability (solid, gas) Extremely flammable aerosol.

Upper/lower flammability or

explosive limits

Not determined.

Vapour pressure Not determined.

Vapour density Not determined.

Relative density Not determined.

Solubility(ies) Not determined.

Partition coefficient Not determined.

Auto-ignition temperature Not determined.

Decomposition Temperature Not determined.

Viscosity Not determined.

Explosive properties Not considered to be explosive.

Oxidising properties Does not meet the criteria for classification as oxidising.

9.2. Other information

Other information No information required.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity See the other subsections of this section for further details.

10.2. Chemical stability

Temporary Line Marker (GB)

Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Flammable/combustible materials. In use may form flammable/explosive vapour-air mixture.

10.4. Conditions to avoid

Conditions to avoid Avoid exposing aerosol containers to high temperatures or direct sunlight. Keep at

temperature not exceeding 50°C/122°F. Pressurised container: may burst if heated Static electricity and formation of sparks must be prevented. Do not pierce or burn, even after use.

10.5. Incompatible materials

Materials to avoid Keep away from oxidising materials, heat and flames.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅o) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Genotoxicity - in vivoBased on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

Based on available data the classification criteria are not met.

development

Specific target organ toxicity - single exposure

Temporary Line Marker (GB)

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

Inhalation Vapours/aerosol spray may irritate the respiratory system.

Ingestion May cause discomfort if swallowed.

Skin contact Prolonged or repeated contact with skin may cause irritation, redness and dermatitis.

Eye contact Vapour or spray in the eyes may cause irritation and smarting.

Toxicological information on ingredients.

Dimethyl ether

Toxicological effects Not regarded as a health hazard under current legislation.

Acute toxicity - inhalation

Notes (inhalation LC₅o) LC₅o 164000 ppm, Inhalation, Rat REACH dossier information. Based on available

data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative. REACH dossier information. Based on available data the

classification criteria are not met.

Genotoxicity - in vivoGenome mutation: Negative. REACH dossier information. Based on available data

the classification criteria are not met.

Carcinogenicity

Carcinogenicity NOAEL 2.5%, Inhalation, Rat REACH dossier information. Based on available data

the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity -

fertility

Screening - NOAEL 2.5 %, Inhalation, Rat P REACH dossier information. Based on

available data the classification criteria are not met.

Reproductive toxicity -

development

Developmental toxicity:, Teratogenicity: - NOAEL: 40000 ppm, Inhalation, Rat No

evidence of reproductive toxicity in animal studies.

Ethanol

Acute toxicity - oral

Acute toxicity oral (LD50

mg/kg)

10,470.0

Species Rat

Notes (oral LD₅₀) REACH dossier information. Based on available data the classification criteria are

not met.

ATE oral (mg/kg) 10,470.0

Acute toxicity - inhalation

Temporary Line Marker (GB)

Acute toxicity inhalation

(LC₅₀ vapours mg/l)

124.7

Species Rat

Notes (inhalation LC₅₀) REACH dossier information. Based on available data the classification criteria are

not met

124.7

ATE inhalation (vapours

Skin corrosion/irritation

mg/l)

Animal data Dose: 0.2 ml, 24 hours, Rabbit Primary dermal irritation index: 0 / 8 REACH dossier

information. Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation

Dose: 0.1 mL, 1 day, Rabbit REACH dossier information. Irritating to eyes.

Respiratory sensitisation

Respiratory sensitisation No information available.

Skin sensitisation

Skin sensitisation Local Lymph Node Assay (LLNA) - Mouse: Not sensitising. REACH dossier

information. Read across data. Based on available data the classification criteria

are not met.

Germ cell mutagenicity

Genotoxicity - in vitroGene mutation: Negative. REACH dossier information. Based on available data the

classification criteria are not met.

Genotoxicity - in vivo Chromosome aberration: Negative. REACH dossier information. Based on available

data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity IARC Group 1 Carcinogenic to humans.

Reproductive toxicity

Reproductive toxicity -

fertility

Two-generation study - NOAEL 15 %, Oral, Mouse P REACH dossier information.

Reproductive toxicity -

development

Maternal toxicity: - NOAEL: 16000 ppm, Inhalation, Rat REACH dossier information.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure LOAEL 4 mL/Kg, Oral, Rat REACH dossier information. Based on available data

the classification criteria are not met.

Aspiration hazard

Aspiration hazard Not anticipated to present an aspiration hazard, based on chemical structure.

SECTION 12: Ecological Information

Temporary Line Marker (GB)

12.1. Toxicity

Ecological information on ingredients.

Dimethyl ether

Toxicity Aquatic toxicity is unlikely to occur.

Acute toxicity - fish LC₅₀, 96 hours: >4100 mg/l, Poecilia reticulata (Guppy)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: >4400 mg/l, Daphnia magna

Ethanol

Toxicity Based on available data the classification criteria are not met.

Acute toxicity - fish LC₅₀, 96 hours: 14200 mg/l, Pimephales promelas (Fat-head Minnow)

REACH dossier information.

Acute toxicity - aquatic

invertebrates

LC₅o, 48 hours: 5012 mg/l, Ceriodaphnia dubia

REACH dossier information.

Acute toxicity - aquatic

plants

EC₅₀, 72 hours: 11.5 mg/l, Chlorella vulgaris

REACH dossier information.

Chronic toxicity - aquatic

invertebrates

NOEC, 9 days: 9.6 mg/l, Daphnia magna

REACH dossier information.

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Ecological information on ingredients.

Dimethyl ether

Persistence and

degradability

No biodegradation observed under test conditions.

Phototransformation Water - DT₅₀ : <8 days

Biodegradation Water - Degradation 5%: 28 days

Ethanol

Biodegradation Water - Degradation (74%): 10 days

REACH dossier information.

The substance is readily biodegradable.

Chemical oxygen demand 1.99 g O₂/g substance REACH dossier information.

12.3. Bioaccumulative potential

Partition coefficient Not determined.

Ecological information on ingredients.

Dimethyl ether

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient log Pow: 0.07

Temporary Line Marker (GB)

Ethanol

Partition coefficient log Pow: - 0.35 REACH dossier information.

12.4. Mobility in soil

Mobility No data available.

Ecological information on ingredients.

Dimethyl ether

Mobility The product is soluble in water. The product contains volatile substances which

may spread in the atmosphere.

518.6 Pa m3/mol @ 25°C Henry's law constant

Ethanol

Mobility The product is water-soluble and may spread in water systems.

Surface tension 24.5 mN/m @ 20°C/68°F REACH dossier information.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

Ecological information on ingredients.

Dimethyl ether

Results of PBT and vPvB

This substance is not classified as PBT or vPvB according to current EU criteria.

assessment

Ethanol

Results of PBT and vPvB This substance is not classified as PBT or vPvB according to current EU criteria.

assessment

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible.

Residues and empty containers should be taken care of as hazardous waste according to

local and national provisions.

Disposal methods Collect and place in suitable waste disposal containers and seal securely. Dispose of

contents/container in accordance with national regulations. Do not empty into drains.

Do not pressurise, cut, weld, drill, grind or otherwise expose containers to heat or sources of ignition. Empty containers must not be punctured or incinerated because of the risk of an

explosion.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

Temporary Line Marker (GB)

UN No. (IMDG) 1950 UN No. (ICAO) 1950 UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name

AEROSOLS

(ADR/RID)

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) Aerosols, flammable

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels



14.4. Packing group

ADR/RID packing group None

IMDG packing group None

ICAO packing group None

ADN packing group None

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Temporary Line Marker (GB)

National regulations EH40/2005 Workplace exposure limits.

The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Commission Regulation (EU) No 2015/830 of 28 May 2015.

Council Directive of 20 May 1975 on the approximation of the laws of the Member States

relating to aerosol dispensers (75/324/EEC) (as amended).

Directive 2012/18/EU of the European Parliament and of the Council of 4 July 2012 on the control of major-accident hazards involving dangerous

substances

P3a - Lower tier 150 tonnes, Upper tier 500 tonnes.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms ATE: Acute Toxicity Estimate.
used in the safety data sheet DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

NOEC: No Observed Effect Concentration.

NOAEL: No Observed Adverse Effect Level.

LC₅o: Lethal Concentration to 50 % of a test population.

EC50: 50% of maximal Effective Concentration.

Classification abbreviations

and acronyms

Aerosol = Aerosol

Flam. Gas = Flammable gas

Press. Gas, Liquefied = Gas under pressure: Liquefied gas

General information For Industrial-Professional Use Only

Classification procedures according to Regulation (EC)

1272/2008

Aerosol 1 - H222, H229: Expert judgement.

Revision date 03/04/2017

Revision 1

Supersedes date 07/06/2016

SDS number 5538

Hazard statements in full H220 Extremely flammable gas.

H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour.

H229 Pressurised container: may burst if heated

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

Temporary Line Marker (GB)

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.